

ADL67

(HN359)



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel, long distance use;
- » Suitable for good road surface;
- » M+S pattern and great anti-wearing character;
- » With great grip ability and excellent traction character;



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
295/60R22.5*	18	3250	3000	900	900	149/146L	150/147K	18	√	I	√
295/80R22.5*	18	3550	3250	900	900	152/149M		18	√		√
315/70R22.5*	18	3450	3150	830	830	152/148M	154/150L	18	√		√
315/80R22.5*	18	3750	3450	830	830	154/151M	156/150L	18	√		√
315/60R22.5#	20	3550	3150	900	900	152/148L		18	√		√

» * refers to pattern ADL67 # refers to pattern HN359

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

