

ADR35



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel for regional use;
- » Suitable for highway and good condition;
- » M+S pattern, with good grip character and traction character;
- » Good anti-wearing character, long mileage.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
205/75R17.5	14	1550	1450	760	760	124/122M		16	√		√
215/75R17.5	16	1750	1600	830	830	127/124M		16	√	I	√
215/75R17.5	18	2180	2060	830	830	135/133J		16	√	I	√
225/75R17.5	16	1850	1750	830	830	129/127M		17	√		√
235/75R17.5	16	2000	1900	830	830	132/130M		17	√	I	√
235/75R17.5	18	2725	2575	900	900	143/141J		17	√	I	√
245/70R17.5	18	2120	2000	900	900	136/134M		16.5	√	I	√
285/70R19.5	16	2650	2430	830	830	144/142M	145/143L	17	√		√
9.5R17.5	18	2240	2120	900	900	136/134M		16	√		√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

