

AGB20

(AGB20+)



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel, urban road use;
- » High wear resistance performance provides good traction performance;
- » The optimized footprint provides the good handling performance and the long life use;
- » Special stone ejector platforms design, prevent the road hazard



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
11R22.5*	16	3000	2725	830	830	146/143J	151/148E	20			√
215/75R17.5#	16	1750	1600	830	830	127/124M		13	√	I	√
215/75R17.5#	18	2180	2060	830	830	135/133J		13	√	I	√
275/70R22.5#	18	3150	2900	900	900	148/145J	152/148E	20	√		√
275/70R22.5*	18	3150	2900	900	900	148/145J	152/148E	20	√		√
295/80R22.5#	18	3550	3250	900	900	152/149J	154/150E	20	√	I	√

» * refers to pattern AGB20+ # refers to pattern AGB20

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

