

AGB22



- Recommend to use
- Permitted
- Not recommended to use

- » Steer and trailer wheel, urban road use;
- » Great width of tread running surface provides perfect stability and anti-wear performance;
- » Groove bottom protectors help to defend against stone drilling and improve retread performance;
- » The tread sipes help the heat dissipation, and reduce the noise;
- » Four grooves, provides excellent wet handling performance and perfect heat dissipation performance;
- » High wear resistance compound ensures much longer mileage.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
275/70R22.5	18	3150	2900	900	900	148/145J	152/148E	18			√
305/70R22.5	18	3350	3150	850	850	150/148J	154/150E	19	√		√
305/70R22.5	20	3550	3350	900	900	152/150L		19	√		√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

