

# AGC28



- Recommend to use
- Permitted
- Not recommended to use

- » Steer and trailer wheel, on/off road use;
- » With powerful grip ability and excellent traction character;
- » Low heat generating character and excellent loading capacity.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146K		20			√
215/75R17.5	18	2180	2060	830	830	135/133J		15.5	√	I	√
235/75R17.5	18	2725	2575	900	900	143/141J		16.5	√		√
245/70R17.5	18	2725	2575	900	900	143/141J	144/144F	16.5	√		√
255/70R22.5	16	2500	2300	830	830	140/137M	140/140L	17.5	√		√
265/70R19.5	18	2725	2575	830	830	143/141J		17.5	√		√
275/70R22.5	18	3150	2900	900	900	148/145M		17.5	√	I	√
385/65R22.5	20	4500	----	900	----	160K	158L	16.8	√		√
425/65R22.5	20	5000	----	830	----	165K		16.5	√	I	√
445/65R22.5	20	5600	----	830	----	169K		16.5	√	I	√

## BRISBANE

28 Ashover Rd  
 Rocklea  
 QLD 4106

## MELBOURNE

41 Paraweena Dr  
 Truganina  
 VIC 3029

## SYDNEY

Rear 46 Redfern St  
 Wetherill Park  
 NSW 2164

## PERTH

8 Glassford Rd  
 Kewdale  
 WA 6105

