

AGC51 (AVATAR)



- Recommend to use
- Permitted
- Not recommended to use

- » Steer and trailer wheel for on/off road use;
- » Suitable for mixed road and relatively poor road condition;
- » Great grip ability and excellent traction character;
- » Low heat generating character and excellent loading capacity.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20#	18	3250	3000	930	930	149/146K		20			√
12R22.5*	18	3550	3250	930	930	152/149L		18		I	
6.50R16*	12	1060	925	670	670	110/105K		13			
7.00R16*	14	1320	1180	770	770	118/114L		14.5			√
8.25R16*	16	1800	1600	770	770	128/124L		16			√
11R22.5*	16	3000	2725	830	830	146/143L		20			√

» * refers to pattern AGC51 # refers to pattern AVATAR

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

