



AL36/L3



- » Suitable for loader, bulldozer, earthmover and bridge moved vehicles.
- » Suitable for mines, coal mines and sand conditions.
- » Special compound provides stronger cut and wear resistance.
- » Excellent mud expelled and side skidding resistance on mud, soft and slippery surfaces for improved self-cleaning, flotation and stability.

SIZE	TYPE	A SNOW L2	AE39 L3	AL36 L3	AL37 L3	AL53 L5	AL53+ L5	AL55 L5	AL58 L5	AL59 L5	AS50 L5S
9.00 R20 **	TT										●
12.00 R20 **	TT										●
15.5 R25 **	TL			●							
17.5 R25 **	TL	●		●	●	●					●
18.00 R25 **	TL										●
20.5 R25 **	TL	●		●	●	●			●	●	
23.5 R25 **	TL	●		●	●	●	●			●	●
26.5 R25 **	TL			●	●	●				●	●
29.5 R25 **	TL				●	●					●
650/65 R25 *	TL		●								
750/65 R25 *	TL		●								
35/65 R33 **	TL					●		●		●	
35/65 R33 ***	TL					●		●			

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

