



AR125

- » Directional pattern design provides Good traction.
- » Excellent self-cleaning on muddy surfaces.
- » Special compound ensures optimum cut resistance.

| SIZE | TYPE | AR123 | AR125 | AR126 | AR128 | AR129 | AR158 | R-1B | R-3 | R-4 |
|--------------|-------|-------|-------|-------|-------|-------|-------|------|-----|-----|
| | | R-1 | R-1 | R-1 | R-1 | R-1 | R-1 | R-1 | R-3 | R-4 |
| 10.0/75-15.3 | TT | ● | | | | | | | | |
| 8.3 -20 | TT | | | ● | | | | | | |
| 8.3 -24 | TT | | | ● | | | | | | |
| 9.5 -24 | TT | | | ● | | | | | | |
| 11.2 -24 | TT | | | ● | | | | ● | | |
| 13.6 -24 | TT | | | ● | | | | | | |
| 14.9 -24 | TL | | | | | | | | | ● |
| 15 -24 | TT | | | | | | ● | | | |
| 16.9 -24 | TL | | | | | | | | | ● |
| 19.5L -24 | TL | | | | | | | | | ● |
| 14.9 -26 | TT | | | | | ● | | | | |
| 18.4 -26 | TL | | | | | | | | | ● |
| 23.1 -26 | TL | | | | | | | ● | ● | |
| 11.2 -28 | TT | | | | | | | ● | | |
| 12.4 -28 | TL/TT | | | | ● | | | ● | | |
| 16.9 -28 | TL | | | | | | | ● | | ● |
| 14.9 -30 | TT | | | | | ● | | ● | | |
| 16.9 -30 | TL | | | | | | | ● | | |
| 18.4 -30 | TL | | | | | | | ● | | |
| 16.9 -34 | TL/TT | ● | | | | | | ● | | |
| 18.4 -34 | TL | | | | | | | ● | | |
| 18.4 -38 | TL/TT | | ● | | | | | ● | | |

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

