



AS522/L5S



- » Special compound designed provides optimum cut and wear resistance.
- » Extra thickened tread increases rock puncture resistance.
- » Special sidewall structure designed gives sidewall a optimum protection.
- » Suitable for underground mines which contain sharp rock on the sidewall.

SIZE	TYPE	G-2	G-13	G-2	G-3	G-12	G-14	G-15	G-26	G-12	G-1A	G-24	G-1A	AS522
		L2	L2	L3	L3	L3	L3	L3	L3	L3	L4	L4S	L5	L5S
10.00 -20	TT			●							●			
12.00 -20	TT												●	
12.00 -24	TT			●							●		●	
14.00 -24	TL/TT					●					●			
15.5 -25	TL/TT		●			●								
17.5 -25	TL/TT		●			●			●			●	●	●
18.00 -25	TL	●											●	
20.5 -25	TL/TT		●		●		●		●			●		
23.5 -25	TL/TT		●			●		●	●			●		
26.5 -25	TL					●			●	●		●	●	
29.5 -25	TL					●						●	●	
29.5 -29	TL					●			●	●			●	
45/65 -45	TL											●		

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

