

ASR35



- Recommend to use
- Permitted
- Not recommended to use

- » Steer wheel for regional use;
- » Suitable for driving on good condition;
- » With excellent anti-side-skid character and drainage character



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
205/75R17.5	14	1600	1500	760	760	124/122M		13	√		√
215/75R17.5	16	1750	1600	830	830	127/124M		13	√	I	√
215/75R17.5	18	2180	2060	830	830	135/133J		13	√	I	√
225/75R17.5	16	1850	1750	830	830	129/127M		13	√		√
235/75R17.5	16	2000	1850	830	830	132/129M		13	√	I	√
235/75R17.5	18	2725	2575	830	830	143/141J		13	√	I	√
245/70R17.5	18	2240	2120	900	900	136/134M		13	√		√
6.50R16	12	1060	925	670	670	110/105L		12			
7.00R15	12	1150	1030	670	670	113/109M		12.5			
7.00R16	14	1320	1180	770	770	118/114L		12.5			
7.50R15	14	1500	1320	770	770	122/118M		12.5			
7.50R16	14	1500	1320	770	770	122/118M		12.5			
8.25R16	16	1800	1600	770	770	128/124M		14			

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

