

ATR65



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel for regional use;
- » With excellent grip ability and traction character;
- » Long mileage, anti-wearing character and great high speed driving character



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
245/70R17.5	18	2725	2575	900	900	143/141J	146/146F	11	√	I	√
265/70R19.5	18	2725	2575	830	830	143/141J		13	√	I	√
285/70R19.5	18	3350	3350	830	830	150/148J		14	√	I	√
385/55R19.5	18	4000	----	900	----	156J		15	√	I	√
385/55R22.5	20	4250	----	830	----	158L	160J	16.5	√	I	√
385/65R22.5	20	4500	----	900	----	160K	158L	16.8	√		√
425/65R22.5	20	5000	----	830	----	165K		16.5	√	I	√
445/65R22.5	20	5600	----	830	----	169K		16.5	√		√
9.5R17.5	18	2725	2575	900	900	143/141J		13	√		

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

