



CM-4 **34**

(TRA CODE:L-4)
CONSTRUCTION MINING

Specially designed for big and heavy loaders and graders. Its extra deep, big tread lugs and wide tread offer outstanding resistance to abrasion and cut, and provide a longer tire life. Compared with regular E-3, it is more suitable for services in mining, quarry, gravel, construction, load-and-carry operations in dock and other tough conditions.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
WIDE BASE TIRE												
23.5-25	16	—	Δ	44.5	1.75	19.50/2.5	574	22.6	1613	63.5	9500	300
	20	—	Δ								10900	375
	24	—	Δ								12500	475
	28	—	Δ								13600	550
26.5-25	20	—	Δ	54.0	2.12	22.00/3.0	635	25.0	1717	67.6	13200	350
	24	—	Δ								14000	400
	26	—	Δ								15000	450
	28	—	Δ								15500	475
29.5-25	22	—	Δ	57.0	2.25	25.00/3.5	780	30.7	1920	75.6	15000	325
	28	—	Δ								17500	425
33.25-29	28	—	Δ	57.0	2.25	27.00/3.5	830	32.7	2096	82.5	21200	375
	30	—	Δ								23000	425
37.25-35	36	—	Δ	70.0	2.75	31.00/4.0	998	39.3	2416	95.1	30750	450
	42	—	Δ								33500	525
37.5-39	36	—	Δ	70.0	2.75	32.00/4.5	1016	40.0	2586	101.8	33500	450
	44	—	Δ								37500	550
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	Δ	57.0	2.25	28.00/3.5	861	33.9	2088	82.2	19000	350

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
	30	—	Δ								21800	450
	32	—	Δ								22400	475
40/65-39	30	—	Δ	70.0	2.75	32.00/4.0	1011	39.8	2421	95.3	27250	375
	36	—	Δ								30750	475
105/45-41	52	—	Δ	70.0	2.75	36.00/4.5	1062	41.8	2588	101.9	47850	620

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

