



# CM-5 40

(TRA CODE:L-5) CONSTRUCTION MINING

Premium deep tread specially designed for loaders, 250% deeper tread than E-3/L-3. Its wide tread and gear-type lug design combined with cut resistant tread compound produce superior resistance to cut, wear and tear and offer riding stability without losing any traction capability. Suited for more severe working conditions, such as: power construction, open-pit mine, quarry, construction. Longer life than regular L-3 and L-4 tires and less downtime from more frequent tire changing.



| Tyre Size         | P. R. | Type |    | Tread Depth |      | Standard Rim | Inflated Dimensions |      |                  |      | Load Capacity |               |
|-------------------|-------|------|----|-------------|------|--------------|---------------------|------|------------------|------|---------------|---------------|
|                   |       | TT   | TL | mm          | inch |              | Overall Width       |      | Overall Diameter |      | Loader@10km/h |               |
|                   |       |      |    |             |      |              | mm                  | inch | mm               | inch | Load Kg       | Inflation Kpa |
| REGULAR BASE TIRE |       |      |    |             |      |              |                     |      |                  |      |               |               |
| 12.00-24NHS       | 16    | △    | —  | 61.0        | 2.40 | 8.50         | 343                 | 13.5 | 1283             | 50.5 | 6150          | 675           |
|                   | 20    | △    | —  |             |      |              |                     |      |                  |      | 6900          | 825           |
| 14.00-24NHS       | 20    | △    | —  | 63.5        | 2.50 | 10.00W       | 350                 | 13.8 | 1359             | 53.5 | 8500          | 700           |

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105





| Tyre Size             | P.<br>R. | Type |    | Tread Depth |      | Standard Rim | Inflated Dimensions |      |                  |      | Load Capacity |               |
|-----------------------|----------|------|----|-------------|------|--------------|---------------------|------|------------------|------|---------------|---------------|
|                       |          | TT   | TL | mm          | inch |              | Overall Width       |      | Overall Diameter |      | Loader@10km/h |               |
|                       |          |      |    |             |      |              | mm                  | inch | mm               | inch | Load Kg       | Inflation Kpa |
|                       | 24       | △    | —  |             |      |              |                     |      |                  |      | 9500          | 850           |
| 16.00-25              | 24       | —    | △  | 71.0        | 2.80 | 11.25/2.0    | 409                 | 16.1 | 1488             | 58.6 | 10600         | 650           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 11500         | 750           |
| 18.00-25              | 24       | —    | △  | 78.5        | 3.10 | 13.00/2.5    | 493                 | 19.4 | 1666             | 65.6 | 12500         | 550           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 13600         | 650           |
|                       | 32       | —    | △  |             |      |              |                     |      |                  |      | 15000         | 750           |
| 21.00-25              | 28       | —    | △  | 87.0        | 3.43 | 15.00/3.0    | 617                 | 24.3 | 1796             | 70.7 | 16500         | 575           |
| 54/18-25              | 24       | —    | △  | 63.5        | 2.50 | 14.00        | 432                 | 17.0 | 1361             | 53.6 | 8950          | 655           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 9750          | 760           |
| <b>WIDE BASE TIRE</b> |          |      |    |             |      |              |                     |      |                  |      |               |               |
| 17.5-25               | 16       | —    | △  | 63.5        | 2.50 | 14.00/1.5    | 432                 | 17.0 | 1361             | 53.6 | 7300          | 475           |
|                       | 20       | —    | △  |             |      |              |                     |      |                  |      | 8250          | 575           |
| 20.5-25               | 16       | —    | △  | 71.0        | 2.80 | 17.00/2.0    | 488                 | 19.2 | 1494             | 58.8 | 8250          | 350           |
|                       | 20       | —    | △  |             |      |              |                     |      |                  |      | 9500          | 450           |
|                       | 24       | —    | △  |             |      |              |                     |      |                  |      | 10300         | 525           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 11500         | 625           |
| 23.5-25               | 16       | —    | △  | 78.5        | 3.10 | 19.50/2.5    | 564                 | 22.2 | 1669             | 65.7 | 9500          | 300           |
|                       | 20       | —    | △  |             |      |              |                     |      |                  |      | 10900         | 375           |
|                       | 24       | —    | △  |             |      |              |                     |      |                  |      | 12500         | 475           |
| 26.5-25               | 20       | —    | △  | 87.0        | 3.43 | 22.00/3.0    | 698                 | 27.5 | 1798             | 70.8 | 13200         | 350           |
|                       | 24       | —    | △  |             |      |              |                     |      |                  |      | 14000         | 400           |
|                       | 26       | —    | △  |             |      |              |                     |      |                  |      | 15000         | 450           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 15500         | 475           |
|                       | 32       | —    | △  |             |      |              |                     |      |                  |      | 17000         | 550           |
| 29.5-25               | 22       | —    | △  | 101.5       | 4.00 | 25.00/3.5    | 770                 | 30.3 | 1923             | 75.7 | 15000         | 325           |
|                       | 28       | —    | △  |             |      |              |                     |      |                  |      | 17500         | 425           |
| 29.5-29               | 22       | —    | △  | 101.5       | 4.00 | 25.00/3.5    | 770                 | 30.3 | 2052             | 80.8 | 16000         | 325           |

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105





| Tyre Size                         | P.<br>R. | Type |    | Tread Depth |      | Standard Rim | Inflated Dimensions |       |                  |       | Load Capacity |               |
|-----------------------------------|----------|------|----|-------------|------|--------------|---------------------|-------|------------------|-------|---------------|---------------|
|                                   |          | TT   | TL | mm          | inch |              | Overall Width       |       | Overall Diameter |       | Loader@10km/h |               |
|                                   |          |      |    |             |      |              | mm                  | inch  | mm               | inch  | Load Kg       | Inflation Kpa |
| 28                                | —        | △    |    |             |      |              |                     |       |                  |       | 19000         | 425           |
| 34                                | —        | △    |    |             |      |              |                     |       |                  |       | 21200         | 525           |
| 33.25-29                          | 24       | —    | △  | 101.5       | 4.00 | 27.00/3.5    | 820                 | 32.3  | 2088             | 82.2  | 19500         | 325           |
| 30                                | —        | △    |    |             |      |              |                     |       |                  |       | 23000         | 425           |
| 37.25-35                          | 36       | —    | △  | 114.0       | 4.50 | 31.00/4.0    | 984                 | 38.75 | 2418             | 95.2  | 30750         | 450           |
| 42                                | —        | △    |    |             |      |              |                     |       |                  |       | 33500         | 525           |
| 37.5-39                           | 36       | —    | △  | 114.0       | 4.50 | 32.00/4.5    | 993                 | 39.1  | 2588             | 101.9 | 33500         | 450           |
| 42                                | —        | △    |    |             |      |              |                     |       |                  |       | 36500         | 525           |
| 44                                | —        | △    |    |             |      |              |                     |       |                  |       | 37500         | 550           |
| 52                                | —        | △    |    |             |      |              |                     |       |                  |       | 41300         | 650           |
| 58                                | —        | △    |    |             |      |              |                     |       |                  |       | 44000         | 725           |
| <b>65 SERIES LOW PROFILE TIRE</b> |          |      |    |             |      |              |                     |       |                  |       |               |               |
| 35/65-33                          | 24       | —    | △  | 101.5       | 4.00 | 28.00/3.5    | 853                 | 33.6  | 2088             | 82.2  | 19000         | 350           |
| 30                                | —        | △    |    |             |      |              |                     |       |                  |       | 21800         | 450           |
| 32                                | —        | △    |    |             |      |              |                     |       |                  |       | 22400         | 475           |
| 40/65-39                          | 30       | —    | △  | 114.0       | 4.50 | 32.00/4.0    | 1001                | 39.4  | 2423             | 95.4  | 27250         | 375           |
| 36                                | —        | △    |    |             |      |              |                     |       |                  |       | 30750         | 475           |
| 45/65-45                          | 38       | —    | △  | 118.0       | 4.65 | 36.00/4.5    | 1102                | 43.4  | 2723             | 107.2 | 38750         | 425           |
| 46                                | —        | △    |    |             |      |              |                     |       |                  |       | 43750         | 525           |
| 48                                | —        | △    |    |             |      |              |                     |       |                  |       | 45000         | 550           |
| 52                                | —        | △    |    |             |      |              |                     |       |                  |       | 47300         | 600           |

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

