



CM-5HT

41

(TRA CODE:L-5)

CONSTRUCTION MINING HALF TRACK

WIDE BASE AND 65 SERIES BIAS PLY TIRES FOR LOADER/DOZERS

The CM-5 half track tire gives you the best of both worlds, featuring the large void for traction, the wear potential of a slick tread, special compounds and heavy casing. This tire is an ideal performer both under and above ground. For extended tire life under severe conditions, the CM-5 half track tire will do the job.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Loader@10km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
WIDE BASE TIRE												
29.5-25	22	—	△	101.5	4.00	25.00/3.5	770	30.3	1923	75.7	15000	325
	28	—	△								17500	425
29.5-29	28	—	△	101.5	4.00	25.00/3.5	770	30.3	2052	80.8	19000	425
	34	—	△								21200	525
37.25-35	36	—	△	114.0	4.50	31.00/4.0	984	38.75	2418	95.2	30750	450
	42	—	△								33500	525
37.5-39	36	—	△	114.0	4.50	32.00/4.5	993	39.1	2588	101.9	33500	450
	44	—	△								37500	550
	52	—	△								41300	650
65 SERIES LOW PROFILE TIRE												
35/65-33	24	—	△	101.5	4.00	28.00/3.5	853	33.6	2088	82.2	19000	350
	30	—	△								21800	450
40/65-39	30	—	△	114.0	4.50	32.00/4.0	1001	39.4	2423	95.4	27250	375
	36	—	△								30750	475
45/65-45	38	—	△	118.0	4.65	36.00/4.5	1102	43.4	2723	107.2	38750	425
	52	—	△								47300	600

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

