



DNR (RD)

16

(TRA CODE:E-3) DIRT N
ROCK-ROCK DEFLECTOR

Tires for scrapers. Its design of massive cross lugs and wide ground contact tread provides superior traction and good resistance to heat build-up. Suited for construction, road building and other applications.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
33.25-35	32	—	△	42.5	1.67	27.00/3.5	894	35.2	2215	87.2	16000	325	25750	450
	38	—	△								18000	400	28000	525
37.5-39	36	—	△	46.5	1.83	32.00/4.5	1016	40.0	2520	99.2	21200	325	33500	450
	44	—	△								24300	400	37500	550

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

