



**DNR(Z)II 19**

(TRA CODE:E-3/L-3)DIRT N ROCK(Z TREAD) II

Desinged for mining dump trucks and loaders. Heavy-duty nylon construction provides superior load capacity. The non-directional tread design provides a maximum traction and good resistance to slippage. More suitable for services in constructions, municipal works and dirt and rock working conditions. Good resistance to abrasion and cut. Better resistance to heat build-up than E-4 tires.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Inf.l.kpa	Load kg	Inf.l.kpa
<b>REGULAR BASE TIRE</b>														
12.00-24NHS	16	Δ	Δ	22.0	0.87	8.50	312	12.3	1247	49.1	3250	450	6150	675
	18	Δ	Δ								3450	500	6525	750
	20	Δ	Δ								3650	550	6900	825
	24	Δ	Δ								4000	650	7600	975
14.00-24NHS	16	Δ	Δ	27.0	1.06	10.00W	376	14.8	1368	53.8	4000	375	7300	550
	20	Δ	Δ								4625	475	8500	700
	24	Δ	Δ								5150	575	9500	850
	28	Δ	Δ								5600	650	10000	925
14.00-25NHS	20	Δ	Δ	27.0	1.06	10.00	376	14.8	1368	53.8	4625	475	8500	700
	24	Δ	Δ								5150	575	9500	850
	28	Δ	Δ								5600	650	10000	925
16.00-24	16	Δ	Δ	28.5	1.12	10.00VA	427	16.8	1459	57.4	4875	325	8250	425
	20	Δ	Δ								5450	400	9750	550
	24	Δ	Δ								6000	475	10600	650
18.00-25	24	Δ	Δ	31.5	1.24	13.00/2.5	498	19.6	1618	63.7	7300	425	12500	550
	28	Δ	Δ								8000	500	13600	650
	32	Δ	Δ								8750	575	15000	750
	36	Δ	Δ								9250	625	16000	850
21.00-33	32	Δ	—	35.0	1.38	15.00/3.0	572	22.5	1953	76.9	10300	500	—	—

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Inf.l.kpa	Load kg	Inf.l.kpa
<b>WIDE BASE TIRE</b>														
15.5-25	12	—	Δ	25.0	0.98	12.00/1.3	394	15.5	1278	50.3	3250	250	5600	400
	16	Δ	Δ								3750	325	6750	550
17.5-25	12	Δ	Δ	27.0	1.06	14.00/1.5	445	17.5	1349	53.1	3650	225	6150	350
	16	Δ	Δ								4250	300	7300	475
	20	Δ	Δ								5000	400	8250	575
20.5-25	16	Δ	Δ	29.0	1.14	17.00/2.0	521	20.5	1494	58.8	5450	275	8250	350
	20	Δ	Δ								6000	325	9500	450
	24	Δ	Δ								6700	400	10300	525
23.5-25	16	Δ	Δ	32.0	1.26	19.50/2.5	597	23.5	1618	63.7	6150	225	9500	300
	20	Δ	Δ								7300	300	10900	375
	24	Δ	Δ								8000	350	12500	475
	28	—	Δ								8750	400	13600	550

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

