



DNRZIII 20

(TRA CODE:E-3/L-3)DIRT N ROCK (Z TREAD)III

Designed for mining dump trucks and loaders. Heavy-duty nylon construction provides superior load capacity. The non-directional tread design provides a maximum traction and good resistance to slippage. More suitable for services in constructions, municipal works and dirt and rock working conditions. Good resistance to abrasion and cut. Better resistance to heat build-up.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		T/ @50km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
17.5-25	12	△	△	23.5	0.93	14.00/1.5	445	17.5	1349	53.1	3650	225	6150	350
	16	△	△								4250	300	7300	475
	20	△	△								5000	400	8250	575
	24	—	△								—	—	9050	675
20.5-25	16	△	△	26.0	1.02	17.00/2.0	521	20.5	1494	58.8	5450	275	8250	350
	20	△	△								6000	325	9500	450
	24	△	△								6700	400	10300	525
23.5-25	16	△	△	36.0	1.42	19.50/2.5	597	23.5	1618	63.7	6150	225	9500	300
	20	△	△								7300	300	10900	375
	24	△	△								8000	350	12500	475
	28	△	△								8750	400	13600	550

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

