



FG:01™

DESIGNED FOR STEER AND ALL AROUND FITMENT OF VEHICLES USED IN CONSTRUCTION SITE, FEATURES HIGH RETREADABILITY, RESISTANCE TO LACERATION AND GRIP IN OFF-ROAD, MILEAGE AND ACOUSTIC COMFORT ON ASPHALTED ROAD.



- Increased tread width promotes **mileage**
- Lateral grooves have a built-in step to ease **stone ejection**; protection ribs on sidewalls enhance **resistance to lateral impacts and abrasion**
- Central groove geometry is optimized to avoid stone trapping for better **resistance to lacerations**
- Specific depth indicators **ease regrooving operations**
- Increased land to sea ratio promotes better **performance on asphalted road** and provides better mileage



SIZE	SPEED CODE	MARKINGS	EFFICIENCY LABELS			REMARK
9.00R20 TT	140/137 K	M+S				designed for APAC
10.00R20 TT	146/143 K	M+S				designed for APAC
11.00R20 TT	150/146 K	M+S				designed for APAC
11R22.5 TL	148/145 K	M+S				designed for APAC
12R22.5 TL	152/148 K	3PMSF M+S	D	A	71 dB	
13R22.5 TL	156/150 K	3PMSF M+S	C	B	72 dB	
275/70R22.5 TL	149/146 L	M+S				designed for APAC
295/80R22.5 TL	152/148 L	3PMSF M+S	D	A	73 dB	
315/80R22.5 TL	156/150 K	3PMSF M+S	D	A	71 dB	
385/65R22.5 TL	160 K (158 L)	M+S	D	B	70 dB	AP05

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

