



G-1A/L3S/L4S/L5S



- › Special compound design provides optimum anti-cutting, anti-puncture and wear resistance.
- › Smooth thickened and super thickened tread increases rock puncture resistance.

SIZE	TYPE	G-2	G-13	G-2	G-3	G-12	G-14	G-15	G-26	G-12	G-1A	G-24	G-1A	AS522
		L2	L2	L3	L3	L3	L3	L3	L3	L3	L4	L4S	L5	L5S
10.00 -20	TT			●							●			
12.00 -20	TT												●	
12.00 -24	TT			●							●		●	
14.00 -24	TL/TT					●					●			
15.5 -25	TL/TT		●			●								
17.5 -25	TL/TT		●			●			●			●	●	●
18.00 -25	TL	●											●	
20.5 -25	TL/TT		●		●		●		●			●		
23.5 -25	TL/TT		●			●		●	●			●		
26.5 -25	TL					●			●	●		●	●	
29.5 -25	TL					●						●	●	
29.5 -29	TL					●			●	●			●	
45/65 -45	TL											●		

SIZE	TYPE	G-21	G-12A	G-16	AL358	AL368	AL369	AL388	G-1A	G-24	AL458	G-24+	G-25
		L2	L3	L3	L3	L3	L3	L3	L3S	L4	L4	L5	L5
16/70 -20	TT		●	●									
18 -20	TT	●											
16/70 -24	TT		●										
17.5 -25	TT								●				
20.5-25	TL											●	
23.5 -25	TT				●	●	●	●			●		
35/65 -33	TL									●			●

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

