



G-4B/E4



- » Sturdy and durable carcass.
- » Deep tread pattern with wide running surface provide good cut and wear resistance, improved traffic-ability on gravel road and long service life.
- » Above 18.00-33, which has following three compounds:
 - » Standard compound.
 - » Cut-resistance compound.
 - » Heat-resistance compound.

SIZE	TYPE	G-10	G-12	G-26	G-11A	G-12	G-35	G-4B	AM1	Q-4N	Q-10	Q-22
		E3	E3	E3	E4	E4	E4	E4				
10.00 -20	TT											●
11.00 -20	TT											●
12.00 -20	TT								●			●
14.00 -20	TT										●	
18 -22.5	TL									●		
16.00 -24	TL/TT		●									
16.00 -25	TL/TT		●					●				
18.00 -25	TL/TT	●				●						
21.00 -33	TT		●				●					
21.00 -35	TL				●							
24.00 -35	TL		●									
37.25 -35	TL		●	●								
24.00 -49	TL						●					
30.00 -51	TL		●									
33.00 -51	TL						●					

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

