



G-4C/E4



- » Sturdy and durable carcass.
- » Deep tread pattern with wide running surface provide good cut and wear resistance and improved traffic-ability on gravel and earth surface.
- » Above 18.00-33, which has following three compounds:
 - » Standard compound.
 - » Cut-resistance compound.
 - » Heat-resistance compound.

SIZE	TYPE	G-5	G-6	G-8	G-4D	G-4A	G-4C	G-4E	G-5	G-29	G-31	G-34
		E3	E3	E3	E4	E4	E4	E4	E4	E7	E4	E3
16.00 -20	TL/TT									●		
12.00 -24	TT										●	
14.00 -24	TT	●		●								
13.00 -25	TT	●	●	●								
14.00 -25	TT	●		●					●			
29.5 -25	TL											●
18.00 -33	TL					●						
21.00 -35	TL						●					
24.00 -35	TL					●						
27.00 -49	TL						●	●				
36.00 -51	TL				●							

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

