

HN06



- Recommend to use
- Permitted
- Not recommended to use

- » Steer wheel and trailer wheel, regional use;
- » Suitable for good road surface application;
- » With excellent anti-side-skid character, low rolling resistance;
- » Low heat generating, excellent high speed driving character



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	16	3000	2725	830	830	146/143L		15	√		
10.00R20	18	3250	3000	930	930	149/146L		15			
11R22.5	16	3000	2725	830	830	146/143M		15			
275/80R22.5	16	3075	2800	830	830	149/146L	148/145M	15	√		
285/75R24.5	14	2800	2575	760	760	144/141M		15			
295/75R22.5	14	2800	2575	760	760	144/141M		15	√		
8.25R20	14	2240	2120	830	830	136/134L		13	√		
8.25R20	16	2430	2300	930	930	139/137L		13			
9.00R20	16	2800	2650	900	900	144/142L		14	√		

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

