

HN09



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel;
- » Suitable for mix road and relatively poor road condition;
- » Excellent traction character and passing though character;
- » Good anti-crack and anti-puncture character.
- » M+S pattern, great traction and driving performance.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	16	3000	2725	830	830	146/143K		17	√		√
10.00R20	18	3250	3000	930	930	149/146K		17			√
11.00R20	18	3550	3250	930	930	152/149K		18	√		√
12.00R20	18	3750	3450	830	830	154/151K		18	√		√
7.50R16	14	1500	1320	770	770	122/118L		16			√
8.25R16	14	1700	1500	670	670	126/122L		14.5			√
8.25R16	16	1800	1600	770	770	128/124L		14.5			√
8.25R20	14	2240	2120	830	830	136/134K		15			√
9.00R20	16	2800	2650	900	900	144/142K		16	√		√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

