

# HN10



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel, on/off road use;
- » Suitable for relatively poor road surface application;
- » With excellent grip ability and traction character;
- » Low heat generating character and excellent loading capacity.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146F		22			
11.00R20	18	3550	3250	930	930	152/149F		22	√	I	
11R22.5	16	3000	2725	830	830	146/143G		22		I	
12.00R20	18	3750	3450	830	830	154/151F		23	√	I	
12.00R24	20	4500	4125	900	900	160/157F		23	√	I	
12R22.5	18	3550	3250	930	930	152/149 G		18.5	√	I	
13R22.5	18	3750	3450	830	830	154/151G	156/150F	22.5	√	I	
9.00R20	16	2800	2650	900	900	144/142F		22			
9.00R20	16	2800	2650	900	900	144/142K		16	√		√

## BRISBANE

28 Ashover Rd  
 Rocklea  
 QLD 4106

## MELBOURNE

41 Paraweena Dr  
 Truganina  
 VIC 3029

## SYDNEY

Rear 46 Redfern St  
 Wetherill Park  
 NSW 2164

## PERTH

8 Glassford Rd  
 Kewdale  
 WA 6105

