

# HN230+

(ASR30)



- Recommend to use
- Permitted
- Not recommended to use

- » Steer and trailer wheel, urban road use,
- » Suitable for high speed on good road condition



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
11R22.5*	16	3000	2725	830	830	146/143M	148/145L	16			
255/70R22.5*	18	2650	2430	900	900	142/139M		14.5			√
275/70R22.5*	18	3150	2900	900	900	148/145M		15	√	I	√
10.00R15#	18	3150	2900	860	860	148/145K		13.5		I	√
255/70R22.5#	16	2500	2300	830	830	140/137M	140/140L	14.5	√	I	√
8.25R15#	18	2300	2240	860	860	137/136K		13		I	√

- » \*refers to pattern ASR30 #refers to pattern HN230+

## BRISBANE

28 Ashover Rd  
 Rocklea  
 QLD 4106

## MELBOURNE

41 Paraweena Dr  
 Truganina  
 VIC 3029

## SYDNEY

Rear 46 Redfern St  
 Wetherill Park  
 NSW 2164

## PERTH

8 Glassford Rd  
 Kewdale  
 WA 6105

