

HN257



- Recommend to use
- Permitted
- Not recommended to use

- » Steer wheel for regional use;
- » With excellent anti-side-skid character;
- » Low heat generating, excellent high speed driving character;
- » Wide tread design provides good long mileage and anti-wearing character.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10R22.5	14	2575	2430	790	790	141/139M		14.5	√		√
10R22.5	16	2800	2650	900	900	144/142M		14.5	√		√
11R22.5	16	3000	2725	830	830	146/143M	148/145L	15	√	I	√
11R24.5	16	3250	3000	830	830	149/146M		15		I	
12R22.5	18	3550	3250	930	930	152/149M		16.5	√	I	√
255/70R22.5	16	2500	2300	830	830	140/137M	140/140L	14.5	√	I	√
265/70R19.5	16	2500	2360	830	830	140/138M		13	√	I	√
275/70R22.5	18	3150	2900	900	900	148/145M		15	√	I	√
285/70R19.5	16	2650	2430	830	830	144/142M	145/143L	14	√	I	√
295/60R22.5	18	3250	3000	900	900	149/146L	150/147K	14.5	√	I	√
295/80R22.5	18	3550	3250	900	900	152/149M		15.5	√	I	√
315/70R22.5	18	3450	3150	830	830	152/148M	154/150L	16.5	√	I	√
315/80R22.5	18	3750	3450	830	830	154/151M	156/150L	16.5	√	I	√
315/80R22.5	20	4625	3750	900	900	161/154K	164/162B	16.5		I	√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

