

HN266



- Recommend to use
- Permitted
- Not recommended to use

- » Steer wheel for regional use
- » Suitable for normal and good road condition;
- » Good anti-wearing character;
- » With excellent tear resistance and anti-even wear character.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146K		16	√		
11.00R20	18	3550	3250	930	930	152/149K		16.5	√		
11R22.5	16	3000	2725	830	830	146/143L		18.5			
11R24.5	16	3250	3000	830	830	149/146L		18.5			
315/80R22.5	18	3750	3450	830	830	154/151L	156/150K	18.5	√		
315/80R22.5	20	4625	3750	900	900	161/154K		18.5			

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

