

HN306



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel for regional use;
- » With excellent grip ability and traction character;
- » Long mileage, anti-wearing character and great high speed driving character



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146K		17.5	√		√
11.00R20	18	3550	3250	930	930	152/149K		18.5			√
11R22.5	16	3000	2725	830	830	148/144M		20.6	√		√
11R24.5	16	3250	3000	830	830	149/146L		20.6			√
12.00R20	22	4250	3875	970	970	158/155J		19			√
12R22.5	18	3550	3250	930	930	152/149M		20.6			√
275/80R22.5	16	3075	2800	830	830	149/146L	148/145M	20.6	√		√
285/75R24.5	14	2800	2575	760	760	144/141M		20.6			√
295/75R22.5	14	2800	2575	760	760	144/141M		20.6	√		√
9.00R20	16	2800	2650	900	900	144/142M		17	√		√
9.00R20	18	3150	2800	930	930	148/144J		17			√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

