

HN352



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel for mixed road surface and poor road condition.
- » Big block design help increase driving ability on mixed road condition and improve grip and traction performance.
- » Open shoulder design prevents uneven wear and improves heat dissipation ability.
- » Reinforced tyre carcass and bead improves the tyre load capacity
- » Special tread compound offers excellent wear resistance and high mileage.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146K		20.5			√
11R22.5	16	3000	2725	830	830	146/143K		24			√
13R22.5	18	3750	3450	830	830	154/151K	156/150G	24	√	I	√
295/80R22.5	18	3550	3250	900	900	152/149K		24			√
315/80R22.5	18	3750	3450	830	830	156/150K		23	√		√
315/80R22.5	20	4125	3750	900	900	157/154K		23			√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

