

HN355



- Recommend to use
- Permitted
- Not recommended to use

- » Drive wheel, regional use;
- » M+S pattern, with good traction character, excellent anti-wear character;
- » Low heat generating, good high speed driving character.



Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20	18	3250	3000	930	930	149/146L		20			√
10R22.5	16	2800	2650	900	900	144/142M		15.5	√		√
11R22.5	16	3000	2725	830	830	146/143M	148/145L	22.5	√		√
12R22.5	18	3550	3250	930	930	152/149M		23	√	I	√
255/70R22.5	16	2500	2300	830	830	140/137M	140/140L	20	√	I	√
265/70R19.5	16	2500	2360	830	830	140/138M		16.5	√	I	√
275/70R22.5	18	3150	2900	900	900	148/145M		20	√		√
295/60R22.5	18	3250	3000	900	900	149/146L	150/147K	22.5	√	I	√
295/80R22.5	18	3550	3250	900	900	152/149M		23	√	I	√
315/70R22.5	18	3450	3150	830	830	152/148M	154/150L	22.5	√		√
315/80R22.5	18	3750	3450	830	830	154/151M	156/150L	23	√	I	√
315/80R22.5	20	4125	3750	900	900	157/154M		23	√	I	√

BRISBANE

28 Ashover Rd
 Rocklea
 QLD 4106

MELBOURNE

41 Paraweena Dr
 Truganina
 VIC 3029

SYDNEY

Rear 46 Redfern St
 Wetherill Park
 NSW 2164

PERTH

8 Glassford Rd
 Kewdale
 WA 6105

