









**HN377**      
 (SIKANDAR)



-  Recommend to use
-  Permitted
-  Not recommended to use

- » Drive wheel, long distance use;
- » Suitable for high speed on good road surface;
- » With good wear resistance and anti-side-skid character;
- » Low heat generating, excellent anti-wear character.

Size	Ply Rating	Single Max. Load(kg)	DualMax. Load(kg)	Single Max Pressure(kPa)	Dual Max Pressure(kPa)	LI/SS	Second. LI/SS	Tread depth	ECE	Inmetro	M+S
								(mm)			
10.00R20#	18	3250	3000	930	930	149/146K		20.5			√
11R22.5*	16	3000	2725	830	830	146/143L	148/145K	23			√
11R24.5*	16	3250	3000	830	830	149/146L		23		I	√
285/75R24.5*	14	2800	2575	760	760	144/141L		23			√
295/75R22.5*	14	2800	2575	760	760	144/141L		23			√

» \* refers to pattern HN377 # refers to pattern SIKANDAR

**BRISBANE**

28 Ashover Rd  
 Rocklea  
 QLD 4106

**MELBOURNE**

41 Paraweena Dr  
 Truganina  
 VIC 3029

**SYDNEY**

Rear 46 Redfern St  
 Wetherill Park  
 NSW 2164

**PERTH**

8 Glassford Rd  
 Kewdale  
 WA 6105

