



## JDS65

• Suitable Conditions



Suitable 



• Long Tread Life

Super wide and wear resistant tread provides a longer tread life for longer travel (an extra 20% compared to the original).

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
295/60R22.5	9.00	18	3350	3075	7390	6780	900	900	130	130	150	147	17	L	926	292
315/60R22.5	9.75	18	3550	3150	7825	6945	900	900	130	130	152	148	18	L	950	313
315/70R22.5	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	18	M	1020	312
315/70R22.5	9.00	18	4000	3350	8820	7385	900	900	130	130	156	150	18	L	1020	312
315/70R22.5	9.00	18	3750	3350	8265	7385	900	900	130	130	154	150	18	L	1020	312
295/80R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	17	M	1050	298
295/80R22.5	9.00	16	3550	3150	7825	6945	850	850	125	125	152	148	17	M	1050	298
295/80R22.5	9.00	18	3550	3250	7825	7165	900	900	130	130	152	149	17	L	1050	298
315/80R22.5	9.00	18	4000	3350	8820	7385	850	850	123	123	156	150	18	L	1082	312
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	18	L	1082	312
315/80R22.5	9.00	20	4000	3650	8820	8050	850	850	120	120	156	153	18	K	1082	312

1mm=0.039inch

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

