



# JT578



High Speed



Reduced Noise



High Durability



High Strength

Suitable



- Reduced fuel consumption
- Low noise emissions
- High wear-resistance
- Good cost performance

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Infated Tyre Dimention (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	15	M	1054	279
11R22.5	8.25	16	3150	2900	6945	6395	840	840	120	120	148	145	15	M	1054	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	15	L	1085	300
12R22.5	9.00	18	3550	3150	7825	6945	850	850	125	125	152	148	15	L	1085	300
12R22.5	9.00	18	3550	6945	7825	3150	850	850	125	125	152	148	15	L	1085	300

1mm=0.039inch

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105

