



JY522



Suitable 



- High scrub resistance
- Low noise emissions
- Cool running
- Long tread life

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D			D	B
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	15.5	M	1054	279
11R22.5	8.25	16	3000	2725	6610	6010	830	830	120	120	146	143	15.5	L	1054	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	16	L	1085	300
12R22.5	9.00	18	3550	3250	7825	7165	930	930	135	135	152	149	16	K	1085	300
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	16	L	1076	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	16	L	1076	312

1mm=0.039inch

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

