



JT560

Suitable




■ Medium and long mileage running on paved road / Recommended Position: Trailer Position



• Wide tread and four straight groove pattern provides excellent handling, safety, and water drainage.

• Wear-resistance rubber and optimised pattern design ensure longer mileage.

• Optimized tire shoulder and unique notch design effectively reduce abnormal tread wear.



Size	Standard Rim	PR	Load		Pressure		Load Index	TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG	lbs	kPa	psi				D	B
385/55R22.5	12.25	18	4250	9370	850	123	158	14.5	L	1002	376
385/55R22.5	12.25	20	4500	9920	900	130	160	14.5	K	1002	376
385/65R22.5	11.75	18	4250	9370	830	120	158	15.5	L	1072	389
385/65R22.5	11.75	20	4500	9920	900	130	160	15.5	K	1072	389
435/50R19.5	14.00	20	4500	9920	900	130	160	12.5	J	936	436
445/45R19.5	15.00	20	4500	9920	900	130	160	13.0	J	899	446

1mm=0.039inch

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

