

# ALL POSITION



## JY566



Reduced Noise High Durability High Strength Wide Section



- High durability
- Long tread life
- Cool running

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
10.00R20	7.5	16	3000	2725	6605	6010	830	830	120	120	146	143	15	K	1054	278
10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	15	K	1054	278
11.00R20	8.0	16	3350	3075	7390	6780	830	830	120	120	150	147	15.5	K	1085	293
11.00R20	8.0	18	3550	3250	7830	7160	930	930	135	135	152	149	15.5	K	1085	293
12.00R20	8.5	18	3750	3450	8270	7610	830	830	120	120	154	151	16.5	K	1125	315
12.00R20	8.5	20	4000	3650	8820	8050	900	900	130	130	156	153	16.5	K	1125	315
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	16	M	1054	279
11R22.5	8.25	16	3000	2725	6610	6010	830	830	120	120	146	143	16	L	1054	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	18	L	1085	300
12R22.5	9.00	18	3550	3250	7825	7165	930	930	135	135	152	149	18	K	1085	300
13R22.5	9.75	18	3750	3450	8270	7605	830	830	120	120	154	151	18	K	1124	320
13R22.5	9.75	20	4000	3350	8820	7390	900	900	130	130	156	150	18	J	1124	320
295/80R22.5	9.00	18PR	3550	3250	7825	7165	850	850	125	125	152	149	17.5	M	1044	298
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	17	L	1076	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	17	L	1076	312

1mm=0.039inch



## JY596



High Durability High Strength



- The JY596 is an all-position tire approved for regional applications on paved roads with a long tread life to provide better cost-efficiency.

- The widened shoulder and unique shallow groove design on the shoulder provide for cool running and prevent irregular wear.

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
11.00R20	8.0	18	3550	3250	7830	7160	930	930	135	135	152	149	15.5	K	1085	293
12.00R20	8.5	18	3750	3450	8270	7610	830	830	120	120	154	151	16	K	1125	315

1mm=0.039inch