



JY706



High Durability



High Strength

Suitable



- The special tread design effectively improves self-cleaning and reduces stone retention.
- The deepened groove pattern provides longer mileage and longer tread life.

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
9.00R20	7.0	14	2575	2430	5660	5340	790	790	115	115	141	139	16	K	1030	259
9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	16	J	1030	259
10.00R20	7.5	16	3000	2725	6605	6010	830	830	120	120	146	143	17.5	K	1065	278
10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	17.5	K	1065	278
11.00R20	8.0	16	3350	3075	7390	6780	830	830	120	120	150	147	17.5	K	1096	293
11.00R20	8.0	18	3550	3250	7830	7160	930	930	135	135	152	149	17.5	K	1096	293
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	17.5	M	1065	279
11R22.5	8.25	16	3150	2900	6945	6395	840	840	120	120	148	145	17.5	L	1065	279
11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	20	L	1116	279
11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	20	L	1116	279
295/75R22.5	9.00	14	2800	2575	6175	5675	760	760	110	110	144	141	20	K	1020	298
295/75R22.5	9.00	16	3000	2725	6610	6005	830	830	120	120	146	143	20	K	1020	298
285/75R24.5	8.25	14	2800	2575	6175	5675	760	760	110	110	144	141	20	J	1056	283
285/75R24.5	8.25	16	3075	2800	6780	6175	830	830	120	120	147	144	20	J	1056	283

1mm=0.039inch

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

