




JY708



High Speed




High Durability



Excellent Grip

Suitable ●



• Excellent traction and high durability

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
10.00R20	7.5	16	3000	2725	6605	6010	830	830	120	120	146	143	23.5	K	1065	278
10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	23.5	K	1065	278
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	23.5	L	1065	279
11R22.5	8.25	16	3150	2900	6945	6395	840	840	120	120	148	145	23.5	L	1065	279
295/75R22.5	9.00	14	2800	2575	6175	5675	760	760	110	110	144	141	23.5	K	1020	298
295/75R22.5	9.00	16	3000	2725	6610	6005	830	830	120	120	146	143	23.5	K	1020	298
285/75R24.5	8.25	14	2800	2575	6175	5675	760	760	110	110	144	141	23.5	J	1056	283
285/75R24.5	8.25	16	3075	2800	6780	6175	830	830	120	120	147	144	23.5	J	1056	283
11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	23.5	L	1116	279
11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	23.5	L	1116	279

1mm=0.039inch

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

