



# JY719



High Durability



High Strength



- Excellent traction
- High scrub resistance
- Cut resistant

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
7.00R16	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	14	L	775	205
7.50R16	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	15.5	L	811	215
8.25R16	6.50H	14	1700	1500	3750	3310	670	670	97	97	126	122	15.5	L	865	235
8.25R16	6.50H	16	1800	1600	3970	3525	770	770	110	110	128	124	15.5	L	865	235
8.25R20	6.5	16	2430	2300	5360	5070	930	930	135	135	139	137	17	K	974	236
9.00R20	7.0	14	2575	2430	5660	5340	790	790	115	115	141	139	18	K	1030	259
9.00R20	7.0	16	2800	2650	6170	5840	900	900	130	130	144	142	18	K	1030	259
9.5R17.5	6.75	18	2725	5675	6005	2575	875	875	125	125	143	141	17	K	850	240
10.00R20	7.5	16	3000	2725	6605	6010	830	830	120	120	146	143	19	K	1065	278
10.00R20	7.5	18	3250	3000	7160	6610	930	930	135	135	149	146	19	K	1065	278
12.00R24	8.5	18	4250	3875	9370	8540	830	830	120	120	158	155	20	K	1238	315
12.00R24	8.5	20	4500	4125	9920	9090	900	900	130	130	160	157	20	K	1238	315
265/70R19.5	7.50	18	2725	5675	6005	2575	900	900	130	130	143	141	15	K	867	262

1mm=0.039inch

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105

