



JY958



High Speed



High Durability



Excellent Grip

Suitable 



- Excellent traction
- Long tread life

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tyre Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D	S	D				
11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	19.5	L	1065	279
11R22.5	8.25	16	3000	2725	6610	6010	830	830	120	120	146	143	19.5	K	1065	279
12R22.5	9.00	16	3350	3075	7390	6780	830	830	120	120	150	147	20	L	1096	300
12R22.5	9.00	18	3550	3250	7825	7165	930	930	135	135	152	149	20	K	1096	300
295/80R22.5	9.00	18PR	3550	3250	7825	7165	900	900	130	130	152	149	21	L	1044	298
315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	20	L	1082	312
315/80R22.5	9.00	20	4000	3650	8820	8045	850	850	125	125	156	153	20	L	1082	312

1mm=0.039inch

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

