



LG

12

(TRA CODE:L-2、R-4)LOADER/GRADER

Tires for graders, loaders and industrial tractors. The directional lugs produce self-cleaning action and provide excellent traction and flotation on loose soil and sand. It is an economy tire.



TRA CODE L-2 SERIES

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		G/@40km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
WIDE BASE TIRE														
15.5-25	12	△	△	26.5	1.04	12.00/1.3	396	15.6	1257	49.5	2650	250	5600	400
	16	△	△								3225	350	6750	550
17.5-25	12	△	△	26.0	1.02	14.00/1.5	442	17.4	1346	53.0	2900	200	6150	350
	16	△	△								3350	275	7300	475

Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity		
		TT	TL	mm	inch		Overall Width		Overall Diameter		Max @40km/h		
							mm	inch	mm	inch	Load Kg	Inflation Kpa	
14.9-24	6	△	△	26.5	1.04	W12-W13	353	13.9	1245	49.0	1950	170	
	8	△	△								2300	210	
	10	△	△								2600	260	
	12	△	△								2900	290	
16.9-24	8	△	△	26.5	1.04	W15L	422	16.6	1298	51.1	2650	190	
	10	△	△								2900	220	
	12	△	△								3250	260	
	16	△	△								3775	330	
16.9-28	8	△	△	27.5	1.08	W15L-W14L	434	17.1	1374	54.1	2800	190	
	10	△	△								3075	220	
	12	△	△								3450	260	
18.4-24	10	△	△	25.5	1.00	W15L-W16L	478	18.8	1336	52.6	3350	210	
LOW PROFILE TIRE													
17.5L-24	8	△	△	24.0	0.94	W15L	368	14.5	1245	49.0	2430	180	
	10	△	△								2800	220	
	16	—	△								3650	330	
19.5L-24	8	—	△	25.5	1.00	W16L- W15L-W16A	457	18.0	1334	52.5	2725	170	
	10	—	△								3000	190	
	12	—	△								3450	230	

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

