



LGS 13

(TRA CODE:L-2)LOADER GRADER SPECIAL

The angle of the tread lug provides excellent traction and flotation and provides excellent performance for loaders and graders.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity			
		TT	TL	mm	inch		Overall Width		Overall Diameter		G/@40km/h		L/ @10km/h	
							mm	inch	mm	inch	Load kg	Infl.kpa	Load kg	Infl.kpa
REGULAR BASE TIRE														
18.00-25	16	—	△	31.5	1.24	13.00/2.5	531	20.9	1618	63.7	5000	250	10000	375
	20	—	△								5550	300	11500	475
WIDE BASE TIRE														
20.5-25	12	△	△	28.5	1.12	17.00/2.0	523	20.6	1476	58.1	3550	175	6700	250
	16	△	△								4000	225	8250	350
23.5-25	12	△	△	31.5	1.24	19.50/2.5	610	24.0	1621	63.8	4000	150	8000	225
	16	△	△								4750	200	9500	300
	18	△	△								5150	225	10600	350
	20	△	△								5450	250	10900	375

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

