



**MS3 45**

(TRA CODE:L-3S)MINE SLICK

Designed for underground mining in severe service conditions. Its super tough tread compounds and strong nylon construction provide extended tire life. Its slick design offers excellent resistance to cut and wear in underground operations. The MS3 will deliver performance unparalleled by other standard tires.

| Tyre Size                | P. R. | Type |    | Tread Depth |      | Standard Rim | Inflated Dimensions |      |                  |      | Load Capacity |               |
|--------------------------|-------|------|----|-------------|------|--------------|---------------------|------|------------------|------|---------------|---------------|
|                          |       | TT   | TL | mm          | inch |              | Overall Width       |      | Overall Diameter |      | Loader@10km/h |               |
|                          |       |      |    |             |      |              | mm                  | inch | mm               | inch | Load Kg       | Inflation Kpa |
| <b>REGULAR BASE TIRE</b> |       |      |    |             |      |              |                     |      |                  |      |               |               |
| 12.00-20NHS              | 16    | Δ    | Δ  | 22.0        | 0.88 | 8.50         | 315                 | 12.4 | 1173             | 46.2 | 5450          | 675           |
| 12.00-24NHS              | 16    | Δ    | —  | 23.0        | 0.90 | 8.50         | 310                 | 12.2 | 1217             | 47.9 | 6150          | 675           |
|                          | 20    | Δ    | —  |             |      |              |                     |      |                  |      | 6900          | 825           |
|                          | 24    | Δ    | —  |             |      |              |                     |      |                  |      | 7600          | 975           |

| Tyre Size             | P. R. | Type |    | Tread Depth |      | Standard Rim | Inflated Dimensions |      |                  |      | Load Capacity |               |
|-----------------------|-------|------|----|-------------|------|--------------|---------------------|------|------------------|------|---------------|---------------|
|                       |       | TT   | TL | mm          | inch |              | Overall Width       |      | Overall Diameter |      | Loader@10km/h |               |
|                       |       |      |    |             |      |              | mm                  | inch | mm               | inch | Load Kg       | Inflation Kpa |
| 14.00-24NHS           | 20    | Δ    | —  | 25.5        | 1.00 | 10.00W       | 363                 | 14.3 | 1316             | 51.8 | 8500          | 700           |
|                       | 24    | Δ    | —  |             |      |              |                     |      |                  |      | 9500          | 850           |
|                       | 28    | Δ    | —  |             |      |              |                     |      |                  |      | 10000         | 925           |
| 18.00-25              | 24    | Δ    | Δ  | 31.5        | 1.24 | 13.00/2.5    | 493                 | 19.4 | 1605             | 63.2 | 12500         | 550           |
|                       | 32    | Δ    | Δ  |             |      |              |                     |      |                  |      | 15000         | 750           |
|                       | 36    | —    | Δ  |             |      |              |                     |      |                  |      | 16000         | 850           |
| 21.00-25              | 28    | —    | Δ  | 38.0        | 1.50 | 15.00/3.0    | 566                 | 22.3 | 1709             | 67.3 | 16500         | 575           |
|                       | 32    | —    | Δ  |             |      |              |                     |      |                  |      | 17500         | 650           |
|                       | 36    | —    | Δ  |             |      |              |                     |      |                  |      | 18600         | 725           |
| <b>WIDE BASE TIRE</b> |       |      |    |             |      |              |                     |      |                  |      |               |               |
| 17.5-25               | 16    | —    | Δ  | 25.5        | 1.00 | 14.00/1.5    | 427                 | 16.8 | 1321             | 52.0 | 7300          | 475           |
|                       | 20    | —    | Δ  |             |      |              |                     |      |                  |      | 8250          | 575           |
| 23.5-25               | 20    | —    | Δ  | 31.5        | 1.24 | 19.50/2.5    | 576                 | 22.7 | 1613             | 63.5 | 10900         | 375           |
|                       | 24    | —    | Δ  |             |      |              |                     |      |                  |      | 12500         | 475           |
|                       | 28    | —    | Δ  |             |      |              |                     |      |                  |      | 13600         | 550           |
| 26.5-25               | 26    | —    | Δ  | 38.0        | 1.50 | 22.00/3.0    | 663                 | 26.1 | 1714             | 67.5 | 15000         | 450           |
|                       | 32    | —    | Δ  |             |      |              |                     |      |                  |      | 17000         | 550           |
|                       | 40    | —    | Δ  |             |      |              |                     |      |                  |      | 19550         | 700           |
| 29.5-29               | 40    | —    | Δ  | 38.0        | 1.50 | 25.00/3.5    | 787                 | 31.0 | 2047             | 80.6 | 23600         | 625           |

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

