

# HP

# MOZZO 4S+

### Low Failure Solution

- High turn-up belt structure to avoid early damage.

### Transport Efficiency Solution

- Silicious compound to enhance low rolling resistance.

### Noise Reduction Solution

- Optimized pattern pitch to reduce rolling noise.

### All-weather Grip Solution

- Special compound combined with zigzag steel disc to enhance outstanding wet grip.

### Travel Comfort Solution

- Enable special production line of the most advanced equipment to ensure ride comfort.



NO.	Series	Size	SL/XL	Sidewall Type	PR	Rim	Load Index	Speed Rating	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	40"	205/40R17	XL	BSW	-	7.5	84	W	500	1102	340	50	7.8	212	596
2	45"	205/45R16	SL	BSW	-	7.0	83	V	487	1074	350	51	7.8	206	590
3		205/45R16	XL	BSW	-	7.0	87	W	545	1201	340	50	7.8	206	590
4	50"	195/50R15	SL	BSW	-	6.0	82	V	475	1047	350	51	7.8	201	577
5		205/50R16	SL	BSW	-	6.5	87	V	545	1201	350	51	7.8	214	612
6	55"	195/55R15	SL	BSW	-	6.0	85	H	515	1135	350	51	7.8	201	595
7		195/55R15	SL	BSW	-	6.0	85	V	515	1135	350	51	7.8	201	595
8		195/55R16	XL	BSW	-	6.0	91	H	615	1356	340	50	7.8	201	620
9		195/55R16	XL	BSW	-	6.0	91	V	615	1356	340	50	7.8	201	620
10		205/55R16	SL	BSW	-	6.5	91	H	615	1356	350	51	7.8	214	632
11		205/55R16	SL	BSW	-	6.5	91	V	615	1356	350	51	7.8	214	632
12		195/60R15	SL	BSW	-	6.0	88	H	560	1235	350	51	7.8	201	615
13		195/60R15	SL	BSW	-	6.0	88	V	560	1235	350	51	7.8	201	615
14	60"	205/60R14	SL	BSW	-	6.0	88	V	560	1235	350	51	7.8	209	602
15		205/60R15	SL	BSW	-	6.0	91	H	615	1356	350	51	7.8	209	627
16		205/60R15	SL	BSW	-	6.0	91	V	615	1356	350	51	7.8	209	627
17		205/60R16	SL	BSW	-	6.0	92	H	630	1389	350	51	7.8	209	652
18		205/60R16	SL	BSW	-	6.0	92	V	630	1389	350	51	7.8	209	652
19		205/60R16	XL	BSW	-	6.0	96	V	710	1565	340	50	7.8	209	652
20		215/60R16	SL	BSW	-	6.5	95	H	690	1521	350	51	7.8	221	664
21		215/60R16	SL	BSW	-	6.5	95	V	690	1521	350	51	7.8	221	664
22	65"	215/60R16	XL	BSW	-	6.5	99	V	775	1709	340	50	7.8	221	664
23		225/60R16	SL	BSW	-	6.5	98	H	750	1653	350	51	7.8	228	676
24		225/60R16	XL	BSW	-	6.5	102	V	850	1874	340	50	7.8	228	676
25	70"	195/65R15	SL	BSW	-	6.0	91	H	615	1356	350	51	7.8	201	635
26		195/65R15	SL	BSW	-	6.0	91	V	615	1356	350	51	7.8	201	635
27		205/65R15	SL	BSW	-	6.0	94	H	670	1477	350	51	7.8	209	647
28		205/65R15	SL	BSW	-	6.0	94	V	670	1477	350	51	7.8	209	647
29	70"	195/70R14	SL	BSW	-	6.0	91	T	615	1356	350	51	7.8	201	630

### BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

### MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

### SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

### PERTH

8 Glassford Rd  
Kewdale  
WA 6105

