

HP

MOZZO 4S

Low Failure Solution

- High turn-up belt structure to avoid early damage.

Transport Efficiency Solution

- Silicious compound to enhance low rolling resistance.

Noise Reduction Solution

- Optimized pattern pitch to reduce rolling noise.

All-weather Grip Solution

- Special compound combined with zigzag steel disc to enhance outstanding wet grip.



Travel Comfort Solution

- Enable special production line of the most advanced equipment to ensure ride comfort.

NO.	Series	Size	SL/XL	Sidewall Type	PR	Rim	Load Index	Speed Rating	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max. Air Pressure (KPa)	Max. Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	40"	165/40R16	XL	BSW	-	6.0	70	V	335	739	340	50	7.2	170	538
2		165/40R16	XL	BSW	-	6.0	73	V	365	805	340	50	7.2	170	538
3		165/45R16	XL	BSW	-	5.5	74	V	375	827	340	50	7.2	165	554
4	50"	165/50R15	SL	BSW	-	5.0	72	H	355	783	350	51	7.4	170	547
5		165/50R15	SL	BSW	-	5.0	72	V	355	783	350	51	7.4	170	547
6	55"	155/55R14	SL	BSW	-	5.0	69	H	325	716	350	51	7.2	162	526
7		165/55R14	SL	BSW	-	5.0	72	H	355	783	350	51	7.4	170	538
8		165/55R15	SL	BSW	-	5.0	75	H	387	853	350	51	7.2	170	563
9		165/55R15	SL	BSW	-	5.0	75	V	387	853	350	51	7.2	170	563
10		185/55R15	SL	BSW	-	6.0	82	V	475	1047	350	51	7.4	194	585
11		185/55R15	SL	BSW	-	6.0	82	H	475	1047	350	51	7.4	194	585
12	60"	165/60R14	SL	BSW	-	5.0	75	H	387	853	350	51	7.4	170	554
13		185/60R14	SL	BSW	-	5.5	82	H	475	1047	350	51	7.4	189	578
14		185/60R15	SL	BSW	-	5.5	84	H	500	1102	350	51	7.4	189	603
15		185/60R15	XL	BSW	-	5.5	88	H	560	1235	340	50	7.4	189	603
16	65"	175/65R14	SL	BSW	-	5.0	82	H	475	1047	350	51	7.4	177	584
17		175/65R14	SL	BSW	-	5.0	82	T	475	1047	350	51	7.4	177	584
18		175/65R14	XL	BSW	-	5.0	86	T	530	1168	340	50	7.4	177	584
19		175/65R15	SL	BSW	-	5.0	84	H	500	1102	350	51	7.4	177	609
20		185/65R14	SL	BSW	-	5.5	86	H	530	1168	350	51	7.4	189	596
21		185/65R14	SL	BSW	-	5.5	86	T	530	1168	350	51	7.4	189	596
22		185/65R14	XL	BSW	-	5.5	90	S	600	1323	340	50	7.4	189	596
23		185/65R15	SL	BSW	-	5.5	88	H	560	1235	350	51	7.4	189	621
24		185/65R15	SL	BSW	-	5.5	88	T	560	1235	350	51	7.4	189	621
25		185/65R15	XL	BSW	-	5.5	92	T	630	1389	340	50	7.4	189	621
26	70"	145/70R12	SL	BSW	-	4.5	69	T	325	716	350	51	7.2	150	509
27		145/70R13	SL	BSW	-	4.5	71	T	345	761	350	51	7.2	150	534
28		155/70R13	SL	BSW	-	4.5	75	T	387	853	350	51	7.4	157	548
29		165/70R13	SL	BSW	-	5.0	79	T	437	963	350	51	7.4	170	562
30		165/70R13	XL	BSW	-	5.0	83	T	487	1074	340	50	7.4	170	562
31		165/70R14	SL	BSW	-	5.0	81	T	462	1019	350	51	7.4	170	588
32		165/70R14	XL	BSW	-	5.0	85	T	515	1135	340	50	7.4	170	588
33		175/70R13	SL	BSW	-	5.0	82	T	475	1047	350	51	7.4	177	576
34		175/70R14	SL	BSW	-	5.0	84	T	500	1102	350	51	7.4	177	602
35		185/70R13	SL	BSW	-	5.5	86	T	530	1168	350	51	7.4	189	590
36		185/70R14	SL	BSW	-	5.5	88	T	560	1235	350	51	7.4	189	616
37		80"	155/80R13	SL	BSW	-	4.5	79	T	437	963	350	51	7.4	157

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

