

# Neo Allroads S



-  Recommend to use
-  Permitted
-  Not recommended to use




- > Higher load capacity (EURO 6 regulation);
- > Shorten braking distance and enhance driving safety with 4 zig-zag shape grooves and longitudinal ribs design;
- > Good mileage with wider tread and deeper groove design;
- > Reduce noise due to the optimised pattern design;
- > Great steering, dry and wet road handling performance with optimize groove and sipe design;
- > Excellent stone rejection performance with variable angle pattern groove design;
- > Compound with high silica content guarantee great performances in a wide range of temperatures and conditions.

Size	PR	Type	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	M+S	3PMSF	Rolling Resistance	Wet Grip	Noise Value	Noise Grade
215/75R17.5	16	TL	6.00	5.25/6.75	126/124M	-						Available in 2018
235/75R17.5	16	TL	6.75	7.50	132/130M	-						Available in 2018
245/70R17.5	16	TL	7.50	6.75	136/134M	-						Available in 2018
265/70R19.5	16	TL	7.50	8.25	140/138M	-						Available in 2018
285/70R19.5	16	TL	8,25	-	146/144L	-						Available in 2018
295/80R22.5	18	TL	9.00	8.25	154/149M	-						Available in 2018
315/70R22.5	18	TL	9.00	9.75	156/150L	154/150M						Available in 2017
315/80R22.5	18	TL	9.00	9.75	158/150L	154/150M						Available in 2018

**BRISBANE**

28 Ashover Rd  
Rocklea  
QLD 4106

**MELBOURNE**

41 Paraweena Dr  
Truganina  
VIC 3029

**SYDNEY**

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

**PERTH**

8 Glassford Rd  
Kewdale  
WA 6105

