



# Neo Allroads T+



-  Recommend to use
-  Permitted
-  Not recommended to use



- > Trailer use;
- > Good mileage with wider tread and deeper groove design;
- > Better handling performance with zig-zag shape grooves;
- > Less noise and more comfortable with irregular pattern block design;
- > Excellent stone rejection performance with variable angle pattern groove design;
- > Good fatigue resistance with full penetration cord;
- > Compound with high silica content guarantees low rolling resistance and heat generation.

Size	PR	Type	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	M+S	3PMSF	Rolling Resistance	Wet Grip	Noise Value	Noise Grade
285/70R19.5	18	TL	8.25	-	150/148J	-			Available in 2018			
385/55R22.5	20	TL	12,25	11.75	160k	158L			Available in 2018			
385/65R22.5	20	TL	11.75	12.25	160K	158L	√	-	B	C	73	
425/65R22.5	20	TL	12.25	12.25	165K	-			Available in 2017			
445/65R22.5	20	TL	13.00	12.25/14.00	169K	-			Available in 2017			

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105

