



Neo Construct G



-  Recommend to use
-  Permitted
-  Not recommended to use



- > Excellent stone rejection performance with variable angle pattern groove design;
- > Better tear resistance with stiffener of high rigidity pattern block;
- > Special lateral block design offers better traction, avoiding irregular wear;
- > Improving mileage with wider and deeper transverse groove;
- > High loadability with optimised bead design;
- > Good fatigue resistance with full penetration cord;
- > Higher lifecycle performance with dual tread layer.

Size	PR	Type	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	M+S	3PMSF	Rolling Resistance	Wet Grip	Noise Value	Noise Grade
13R22.5	18	TL	9.75	9.00	154/151L	156/150K						Available in 2018
315/80R22.5	18	TL	9.00	9.75	158/150L	154/150K						Available in 2018
425/65R22.5	20	TL	12.25	13.00	165K	-						Available in 2018
445/65R22.5	20	TL	13.00	12.25/14.00	169K	-						Available in 2018

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

