





# Neo Urban G



-  Recommend to use
-  Permitted
-  Not recommended to use



- > Coach and bus suitable for all wheel tyres;
- > Longer mileage with deeper tread depth;
- > Better driving performance with 4 pattern grooves design;
- > Improving heat emission with "S" groove and special deepen sipe design;
- > Excellent sidewall protection design minimizes damage from curb;
- > Better performance of low rolling resistance and heat generation with high silica;
- > Good fatigue resistance with full penetration cord.

Size	PR	Type	Standard Rim	Permitted Rim	LI/SS	Second LI/SS	M+S	3PMSF	Rolling Resistance	Wet Grip	Noise Value	Noise Grade
275/70R22.5	18	TL	8.25	9.00	150/148J	152/148E	√	-	D	E	73	
295/80R22.5	18	TL	9.00	8.25	154/149M	-			Available in 2018			
305/70R22.5	20	TL	9.00	8.25	152/150L	-			Available in 2018			

## BRISBANE

28 Ashover Rd  
Rocklea  
QLD 4106

## MELBOURNE

41 Paraweena Dr  
Truganina  
VIC 3029

## SYDNEY

Rear 46 Redfern St  
Wetherill Park  
NSW 2164

## PERTH

8 Glassford Rd  
Kewdale  
WA 6105

