



PI 54 (TRA CODE:R-4)POWER INDUSTRIAL

For earthmovers, graders, loaders and industrial tractors. The directional opposed lugs produce self-cleaning action and provide excellent traction on loose and soft soil and sand.



Tyre Size	P. R.	Type		Tread Depth		Standard Rim	Inflated Dimensions				Load Capacity	
		TT	TL	mm	inch		Overall Width		Overall Diameter		Max @40km/h	
							mm	inch	mm	inch	Load Kg	Inflation Kpa
14.9-24	8	—	△	25.5	1.00	W12\W13	381	15.01	1258	49.52	2300	210
	10	—	△								2600	260
	12	—	△								2900	290
16.9-24	10	—	△	27.5	1.08	W15L	423	16.67	1328	52.27	2900	220
	12	—	△								3250	260
16.9-28	10	△	△	27.5	1.08	W15L\W14L	418	16.48	1430	56.29	3075	220
	12	△	△								3450	260
LOW PROFILE TIRE												
17.5L-24	10	—	△	26.5	1.04	W15L	470	18.51	1245	49.01	2800	220
	12	—	△								3125	260
19.5L-24	10	—	△	27.5	1.08	W16L\DW16A\W15L	520	20.49	1313	51.71	3000	190
	12	—	△			DW16A					3450	230
21L-24	12	—	△	28.5	1.13	DW18A	552	21.74	1377	54.23	3875	220
	16	—	△								4500	280

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

